



The GT 300 PLUS is a «Gel Timer» to measure all curing times of your products. Combined with disposable measuring systems and temperature control, it adapts to all your expectations for a very competitive cost per measurement.



25

GT-300

C

RHEOLOGY

Available in version with temperature control.

Measure with disposable hooks and cups.

Low volumes.

Software included.

www.lamyrheology.com

Activity domains

Food Industry
Paint / ink / coatings



Building materials

Chemical / petroleum products

Available accessories

Disposable aluminium cups (set of 100) – PN 700011



Gel timer measuring hook (Vol. 50-80mL) standard (set of 100) PN 700010



Gel timer measuring hook low volume (Vol. 35-50mL) (set of 100) PN 700040



Tel : +33 (0)4 78 08 54 06 Fax : +33 (0)4 78 08 69 44 contact@lamyrheology.com 11 A, rue des Aulnes 69410 Champagne au Mont d'Or France

GT 300 PLUS

SPECIFICATIONS

Type of instrument

Rotating springless viscometer / gel timer with 7" Touch screen

Rotation speeds

Unlimited number of speeds between 0.3 and 1500 rpm

Torque range

From 0.05 to 30 mNm

Temperature

The GEL TIMER GT 300 is also available in temperature control version from 15 °C to 300°C (according to models).

Accuracy	Repeatability	
+/- 1 % of the full scale	+/- 0,2 %	

Display

Viscosity – Speed – Torque – Time – Temperature Choice of viscosity units: cP/Poises or mPa.s / Pa.s – Shear rate

Security and confidentiality

An «operator» function allows you to enter a username for your instrument. This user must then be identified using a 4-digit code. There is also a protected mode that locks your measurement conditions.

Language

French/English/Russian/Spanish

Supply voltage

90-240 VAC 50/60 Hz

RS232 Port and USB

4 - 20 mA Printer connection

Analog output

USB Host Port - Compatible PCL/5

Options

Breakable Thermocouple (PN 000645)

Dimensions and weight

Head: L180 x W135 x H250 mm Stand for GEL TIMER: D610 x W340 x H650 mm Weight: 15 kg

Available instruments :

Part Number Instrument	Designation Instrument
N125000	GEL TIMER GT300 without temperature control
N125100	GEL TIMER GT300 electrical heating (room to +300°C)
N125200	GEL TIMER GT300 electrical heating (room to +300°C) with programmer
N125400	GEL TIMER GT300 with Peltier (+15 to + 60°C)
N125500	GEL TIMER GT300 with Peltier (+15 to + 60°C) with programmer



www.lamyrheology.com